Pneumatic table-top test pump // -0.95...160 bar

P160.T



P160.T Basic



P160.T Solid

Highlights

- No contamination of the test sample with oil or water
- Pneumatic up to 160 bar
- Minimal force required to reach 160 bar
- Quick exchange of test samples due to quick couplings
- Fine adjustment valve for exact setting of the test pressure

Technical data	
Type	**P160.T**
Pressure ranges	
Vacuum	-0.95 bar
Overpressure	160 bar
Pressure medium	Air
Connections	
Reference pressure gauge	G¼ with quick coupling
Test sample	G¼ with quick coupling
Basic	
Dimensions	Approx. 470 × 262 × 170 mm
Weight	Approx. 6 kg
Solid	
Dimensions (case)	Approx. 575 x 470 x 230 mm
Weight	Approx. 10.2 kg
+ Adapter kit	Brass chrome plated
+ Seal kit	PA flat gaskets and O-rings

Grubatec AG - Gewerbehaus Ergolz, Wölferstrasse 5 - 4414 Füllinsdorf
Telefon: +41 (0)55 617 00 80 - www.grubatec.ch - sales@grubatec.ch

Article numbers

Order code			
Type	**Version**		**Order number**
P160.T	Lever pump	Basic Solid (incl. case and adapter)	EPPT160EBL0000 EPPT1600BL0000

Grubatec AG - Gewerbehaus Ergolz, Wölferstrasse 5 - 4414 Füllinsdorf
Telefon: +41 (0)55 617 00 80 - www.grubatec.ch - sales@grubatec.ch